

GASOLINE Generator

Technical Data

GENERATOR		HY7000L	HY7000LE
Frequency	Hz	50	50
Rated Power	KVA	5.0	5.0
Max. Power	KVA	5.5	5.5
Voltage	V	220	220
Current	A	25	23.9
Plugs		1x16A / 1x32A	1x16A / 1x32A
Display		LED5/LED3	LED5/LED3
Fuel tank capacity	L	25	25
Fuel consumption @ 100% Load	L/h	2.8	2.8
Sound level @ 7m	dBA	79 (95 Lwa)	79 (95 Lwa)
DC output	V/A	12 / 8.3	12 / 8.3
Battery (Ah)		14	14
ENGINE		IC390	IC390
Engine type		Gasoline	Gasoline
Power	hp	13	13
Start		Manual	Manual/Electric
Displacement	CC	389	389
Oil Capacity	L	1.1	1.1
ALTERNATOR		AL5	AL5
Power	Kw	5	5
Power Factor		1	1
Voltage Regulation		AVR	AVR
DIMENSIONS & WEIGHT			
Net Weight	Kg	82	87
Gross Weight	Kg	85	90
machine size	mm	670x540x555	670x540x555
Dimensions Package	mm	690x560x580	690x560x580
Loading Capacity FCL20/40'HQ		96/272	96/272



LED5
PRECISE OVER LOAD PROTECTION



LED3

Optional Accessories



ATS control box(50A)



Remote controller: 1+2
ATS sensor: 2



Push wheel kit

Electrical standard and options

	HY7000L	HY7000LE
1-phase (2×16A European sockets)	●	●
3-phase (1×16A European socket)	×	×
American;UK;Australian sockets	○	○
Display LED5	●	●
Display LED3	○	○
Precise overload protection	●	●
Common overload protection	○	○
DC output:12V / 8.3A	●	●
Earth connection	●	●
ATS connector	×	○
Remote control	×	○
ATS control box(50A)	×	○

Mechanical standard and options

Frame tube diameter 32mm	●	●
Basic color black	●	●
Alternator: 100% copper /Steel plate Q195	●	●
Alternator: 100% copper /Silicon steel plateDW800	○	○
Push wheel kit	●	●

Option : ○ Standard feature : ● No available : ×

Recommended Spare Parts



Air filter core



Fuel filter element