

GASOLINE Generator

Technical Data

GENERATOR		HY9000LE	HY9000LE-3
Frequency	Hz	50	50
Rated Power	kVA	6.0	7.5 / 2
Max. Power	kVA	6.6	8.3 / 2.2
Voltage	V	220	220/380
Current	A	30	12.6
Plugs		1x16A / 1x32A	1x16A(380)/1x16A(220)
Display		LED5/LED3	LED5/LED3
Fuel tank capacity	L	25	25
Fuel consumption @ 100% Load	L/h	3.0	3.0
Sound level @ 7m	dBA	79	79
DC output	V/A	12 / 8.3	12 / 8.3
Battery (Ah)		14	14
ENGINE		IC425	IC425
Engine type		Gasoline	Gasoline
Power	hp	15	15
Start		Electric	Electric
Displacement	CC	420	420
Oil Capacity	L	1.1	1.1
ALTERNATOR		AL6	AL6-3
Power	kW	6	7.5
Power Factor		1	0.8
Voltage Regulation		AVR	AVR
DIMENSIONS & WEIGHT			
Net Weight	Kg	84	86
Gross Weight	Kg	87	89
machine size	mm	670x540x555	670x540x555
Dimensions Package	mm	690x560x580	690x560x580
Loading Capacity FCL20/40'HQ		96/272	96/272



LED5

Optional Accessories



ATS control box(50A)



Remote controller: 1+2
ATS sensor: 2



Push wheel kit

Electrical standard and options

	HY9000LE	HY9000LE-3
1-phase (2x16A European sockets)	●	×
3-phase (1x16A European socket)	×	●
American;UK;Australian sockets	○	○
Display LED5	●	●
Display LED3	○	○
Precise overload protection	●	●
Common overload protection	○	○
DC output:12V / 8.3A	●	●
Earth connection	●	●
ATS connector	○	○
Remote control	○	○
ATS control box(50A)	○	○

Mechanical standard and options

Frame tube diameter 32mm	●	●
Basic color black	●	●
Alternator: 100% copper /Steel plate Q195	●	●
Alternator: 100% copper /Silicon steel plateDW800	○	○
Push wheel kit	●	●

Option : ○ Standard feature : ● No available : ×

Recommended Spare Parts



Air filter core



Fuel filter element